



Date: _____

Time: _____

Installer: _____

Installation Checklist for I/E JK1001, FJ1001 and TJ1002

Shipping screws have been removed from the top of the unit (JK1001 and FJ1001 only)

GPS antenna is plugged into the correct port

It goes on the right side looking at the rear of the unit, near the USB ports

WiFi antenna is plugged into the correct port

It goes on the left side looking at the rear of the unit, near the AM/FM antenna port

USB extension cord and iPod cable are both wired to the glove box

For I/E JK1001, AM/FM pigtail is connected to the rear of the JK1001 and plugged into the WHITE OEM antenna cable (not the yellow one)

Wiring harness is plugged into the Insane Audio head unit and the OEM wiring harness. All connections are snug.

External mic is connected to the rear of the unit and wired to your desired location

We recommend putting it on the steering column

All additional accessories are connected properly

InsaneTV, rearview camera, rock camera, etc

Blue OBDII adapter is plugged into vehicle OBDII

OEM uConnect module has been removed

Setup Torque for first time use!

Refer to [Quick Start Guide](#) for more details.



JK1001 Installation Checklist (cont)

Verify Insane NavEngine gets a signal

Press NAVI button to load Insane NavEngine. Press on the map button on the left hand side. Does it show your location? (If it is continuously “searching for signal”, check to make sure GPS antenna is plugged into the correct port)

Insert a CD or DVD and verify playback. (JK1001, FJ1001)

If it doesn't go in all the way, check to make sure shipping screws have been removed from the top of the unit

Verify Radio APP is working

If you have poor reception on I/E JK1001, verify that the radio adapter is plugged into the WHITE OEM antenna plug and is connected properly to the JK1001

If installing with backup camera, verify it is working properly

If installing WITHOUT backup camera, verify reverse is working properly

Put the vehicle in reverse. If no backup camera, it should do nothing. If you get a “no signal” error on JK1001, disengage the backup wire at the rear of the JK1001.

Verify Torque app data display

With the vehicle running, launch the Torque app from the main menu. Click on realtime gauges. Does it display live engine data? (if not, refer to the [Quick Start Guide](#) on how to setup Torque for the first time.)

Additional Installation Notes:
